

HOFMANN®



Geodyna 2300M

MOTORCYCLE WHEEL BALANCER

Geodyna 2300M

MOTORCYCLE WHEEL BALANCER

Hofmann has long been the leader in balancing technology. Since 1931, Hofmann balancing machines have been used around the world to balance anything that rotates. These many years of experience led to the development of the 2300M Motorcycle Wheel Balancer. The 2300M is easy to use, accurate, rugged, reliable and affordable.

FEATURES

- Automatic operation - push button start - automatic brake
- One-plane (static) or two-plane (dynamic) balancing
- High performance accuracy with low speed operation
- Quick, simple, accurate wheeling mounting system handles most applications
- Self-calibration by shop personnel eliminating down time and costly service calls
- Special wheel application kits available



Specifications

Shipping weight280lbs
Rim width range1.0" – 20.0"
Rim diameter range8.0" - 30.0"
Max. tire diameter48"
Max. wheel weight150lbs
Electric requirement115V 50/60hz 1ph
Motor1.0 Hp
Cycle timeFrom 6 seconds
Read-outsGram or Ounce
Accuracy1g or 0.05 oz
Balancing Modes10

Standard Accessories

Universal Motorcycle Clamp14mm
Tapered Mounting Cones16mm-45mm
Centering Bushing15,16,17,19mm
Rim width guage, spanner wrench, user calibration weight

Optional Accessories

Harley-Davidson 3/4" Shaft Kit with 1" Adapters2000561
Ducati Wheel Adapter (requires 3/4" shaft)2001355
Honda VFR Wheel Adapter Kit2001355
BMW Wheel Adapter Kit2001140
Automotive Car/Truck Adapter Kit6419107



309 Exchange Avenue • Conway, AR 72032
(800) 251-4500 • (501) 450-1581
Fax (501) 450-2085 • www.hofmann-usa.com



6500 Millcreek Drive • Mississauga, ONT L5N 4G4
(800) 267-2185 • (866) 812-5316
Fax (905) 821-2073 • www.hofmann.ca
E-mail: info@hofmann.ca