HOFMANN®





Geodyna 980L

WHEEL BALANCER



Geodyna 980L

The Hofmann Geodyna 980L is a Heavy Duty Wheel Balancer For Truck, Bus, RV, and Automobile/Light Truck Tires.

• Increase tire tread life

Studies show that 2-Plane/Dynamic wheel balancing of truck tires off-the-vehicle increase their tread life considerably.

Pneumatic wheel lift / No heavy lifting

The pneumatic wheel lift, a standard feature on every 980L, aids in proper wheel mounting and reduces related strains caused by lifting heavy tires.

· Wheel adapters for most applications

The 980L comes standard with truck centering cones for hub piloted wheels, and the professional 4-star/5-star centering arms for stud piloted applications. As a bonus, the 980L comes with the passenger/light truck cones for automotive use.

Self-calibration by operator

The operator can re-calibrate the balancer in two easy steps, ensuring accuracy while saving costly service calls.

Automatic data entry

This time saving feature precisely enters the rim distance and diameter automatically, eliminating operator errors and customer comebacks.

WHEEL BALANCER

Specifications

Shipping weight	690 lbs
Rim width range	2.0" to 20"
Rim diameter range	8.0" to 30"
Max. tire diameter	50"
Max. wheel weight	500 lbs
Electric requirement	115 V, 50/60 Hz, 1 ph
Motor	1.0 Hp
Cycle time	From 7 seconds
Read-outs	gram or ounce
Accuracy	1 g or 0.05 oz
Balancing Modes	10

Standard Accessories

Automotive Cone Kit	1 5/8" to 4 1/2"	
Light Truck Cone	4 1/4" to 6 7/8"	
Budd Wheel Cone	8" to 9"	
Budd Wheel Centering Bushing	220 mm	
Professional 4/5-star centering arm	8-10 lug	
"ZipLock" quick-nut, pressure cup with rubber scratch		

proof cap, rim width gauge and storage pegs

Hofmann manufactures a complete line of wheel service equipment.



Two post lifts, 4-post alignment and midrise lifts.



High performance wheel balancer with all automatic data entry.



Heavy duty tire changer for trucks, buses and off road



309 Exchange Avenue • Conway, AR 72032 (800) 251-4500 • (501) 450-1581 Fax (501) 450-2085 • www.hofmann-usa.com