

HOFMANN®



Monty 1625

TIRE CHANGER

Monty 1625

TIRE CHANGER

THE HOFMANN 1625 HIGH-PERFORMANCE TIRE CHANGER IS DESIGNED FOR HIGH-VOLUME TIRE SHOPS, MULTI-BAY REPAIR SHOPS AND CAR DEALERSHIPS TO SERVICE ALL AUTOMOTIVE AND LIGHT TRUCK TIRES.

- **Large wheel clamping range**
Designed for tires with treads up to 50" in outside diameter, and with up to 26" rim diameter, the 1625 can handle virtually any car or light truck.
- **Dual rim clamping cylinders**
Tight clamping using all four jaws. No damage from rim slippage in the jaws.
- **Four jaw clamping chuck**
The self-centering clamping jaw set clamps rims up to 26" in diameter from the inside and up to 24" from the outside.
- **Powerful two position bead loosening**
6000 lbs. of power at the bead shovel and a range up to 18" wide. The giant two stage pneumatic cylinder provides very precise power toggled with the foot pedal as it is needed. Both the stiffest and the softest sidewalls are a snap. No damage to tires while loosening the beads.
- **Powerful tire inflation system**
Foot pedal operated. Powerful air blast. Each movable jaw is precisely set to the exact position under the rim to seal the tire bead.
- **Built to last**
Heavy, solid 1/2" thick steel clamping table. Rugged steel reinforced chassis. Air cylinders and valves can not rust. A compressed air lubricator and regulator is onboard to keep valves and cylinders maintenance free.
- **Upgradeable**
Add the EASYMONT PRO for an extra set of hands to aid the operator to mount/demount extra stiff, low-profile, high performance and run-flat tires.
- **Wheel protectors**
Guards available to protect even the most expensive alloy wheels and provide extra insurance; with ultimate wheel protection so that even the most expensive wheels can be changed without any additional expense.

Specifications

Shipping weight 620 lbs.
Bead breaker range 2.0" - 18"
Bead loosening power 6,000 lbs.
Max. rim width to 15"
Rim clamping diameter 10.0" to 26.0"
 Inner 12.0" to 26.0"
 Outer 10.0" to 24.0"

Maximum tire diameter 50.0"
Electrical requirements 115v, 1ph, 50/60 hz,
 15 amps
 Other electricals
 available upon request

Drive motor:
 Electric U.S. Built 1 hp motor
 Air Available upon request
Air supply operating range:
 Electric motor 100 to 175 psi
 Air motor 110 to 175 psi

Optional Accessories

EasyMont bead assist device EAA0329G36A
Quick change bead head kit 4028228
Protective insert for mount/demount head (10)
 00087456
Composite mount/demount head, complete
 EAA0247G20A
Replacement Composite head only 0024335
Outside clamping jaws protectors (set 4) .. 4027645
Protective slide cover (1) 0029455
Protective cover for tire lever 0024180
Snap-in jaw protectors (1) 0022129
Protective cover for bead breaker shovel ... 0026582
Wave Tire Tool 0025946
Rim Protector, snap's onto rim, use w/Wave Tool
 4026853
Bead Clamp for performance wheels 6410190
Bead Clamp for run-flat wheels 4024078
Magic Bead Pusher, use w/EasyMont ..EAA0304G92A

Hofmann manufactures a complete line of wheel service equipment.



Imaging & Conventional Equipment



High performance wheel balancers
with all automatic data entry



Combination brake lathes for
rotors, drums and flywheels.

HOFMANN[®]
USA



309 Exchange Avenue • Conway, AR 72032
(800) 251-4500 • (501) 450-1581
Fax (501) 450-2085
www.hofmann-usa.com

HOFMANN[®]
CANADA



6500 Millcreek Drive • Mississauga, ONT L5N 4G4
(800) 267-2185 • (866) 812-5316
Fax (905) 821-2073 • www.hofmann.ca
E-mail: info@hofmann.ca