

HOFMANN®



Monty 1625EM

TIRE CHANGER

Monty 1625EM

TIRE CHANGER

The Hofmann 1625EM High-Performance tire changer is designed for high-volume tire shops, multi-bay repair shops and car dealerships to service standard, low-profile and run-flat tires on cars, SUV's and light trucks

- **EasyMont Pro bead assist**
Holds the bead into drop center allowing one operator to change low-profile high performance tires. Assist operator with bead lubrication, rim clamping, re-loosens beads, and allows easy one operator mounting of stiff upper bead.
- **Large wheel clamping range**
Designed for performance tires with up to 26" rim clamping diameter, the 1625 EM can handle virtually any car, light truck or SUV.
- **Dual rim clamping cylinders**
Dual pneumatic clamping cylinders controls all four clamping jaws. No damage from rim slippage in the jaws.
- **Four jaw clamping chuck**
The self-centering clamping jaw set clamps rims up to 26" in diameter from the inside and up to 24" from the outside.
- **Powerful two position bead loosening**
6000 lbs. of power at the bead shovel and a range up to 18" wide. The giant two stage pneumatic cylinder provides very precise power toggled with the foot pedal as it is needed. Both the stiffest and the softest sidewalls are a snap. No damage to tires while loosening the beads.
- **Powerful tire inflation system**
Foot pedal operated. Powerful air blast. Each movable jaw is precisely set to the exact position under the rim to seal the tire bead.
- **Built to last**
Heavy, solid 1/2 thick steel clamping table. Rugged steel reinforced chassis. All cylinders and valves can not rust. A compressed air lubricator and regulator is onboard to keep valves and cylinders maintenance free.
- **Wheel protectors**
Guards included to protect even the most expensive alloy wheels and provide extra insurance with ultimate wheel protection so that even the most expensive wheels can be changed without additional expense.

Hofmann manufactures a complete line of wheel service equipment.



Imaging & Conventional Equipment



High performance wheel balancers with all automatic data entry



Combination brake lathes for rotors, drums and flywheels.

Specifications

Shipping weight 805 lbs.
Bead breaker range 2.0" - 18"
Bead loosening power 6,000 lbs.
Max. rim width to 15"
Rim clamping diameter 10.0" to 26.0"
 Inner 12.0" to 26.0"
 Outer 10.0" to 24.0"
With optional adapter
Maximum tire diameter 42.0"
Electrical requirements 115v, 1ph, 50/60 hz,
 15 amps
 Other electricals
 available upon request

Drive motor:

Electric U.S. Built 1 hp motor
Air Available upon request

Air supply operating range:

Electric motor 100 to 175 psi
Air motor 110 to 175 psi

Standard Equipment/Wheel Protectors

EasyMont Pro, bead assist tool ..EAA0329G36A
Quick change head tool4028228
Composite mounting headEAA0247G20A
Protective cover for tire tool0024180
Clamping jaw protectors0027671
Mounting head protector0022129
Bead loosener cover0026582
Snap-on rim protector4026853

Optional Accessories

Protective insert for mount/demount head (10)
 00087456
Replacement Composite head only ...0024335
Wave Tire Tool0025946
Bead Clamp for performance wheels ..6410190
Bead Clamp for run-flat wheels4024078
Magic Bead Pusher, use w/EasyMont
 EAA0304G92A
Hex Bar with roller attachment ..EAA0329G92A
Bead Breaker Disc, use with hex bar
 EAA0304G43A

HOFMANN®

USA

309 Exchange Avenue • Conway, AR 72032

(800) 251-4500 • (501) 450-1581

Fax (501) 450-2085

www.hofmann-usa.com



HOFMANN®

CANADA

6500 Millcreek Drive • Mississauga, ONT L5N 4G4

(800) 267-2185 • (866) 812-5316

Fax (905) 821-2073 • www.hofmann.ca

E-mail: info@hofmann.ca

