

HOFMANN®



Monty 3300/3300EM

TIRE CHANGER

Monty 3300/3300EM

TIRE CHANGER

The Hofmann 3300 and 3300EM high-performance tire changers are designed for high-volume tire shops, multi-bay repair shops and car dealerships to service standard, low-profile and run-flat tires on cars, SUV's and light trucks.

- Large wheel clamping range**
 Designed for performance tires with up to 24" in rim clamping diameter, the 3300/3300EM can change virtually any car, light truck or SUV tire.
- Dual rim clamping cylinders**
 Dual pneumatic clamping cylinders control all four clamping jaws. No damage from rim slippage in the jaws.
- Powerful two-position bead breaker**
 6000 lbs. of power at the bead shovel and arange up to 18" wide. The two stage pneumatic cylinder provides very precise power toggled with the foot pedal as it is needed. Both the stiffest and the softest sidewalls are a snap. No damage to tires while loosening the bead.
- Powerful tire inflation system**
 Foot pedal operated. Powerful air blast. Each movable jaw is precisely set to the exact position under the rim to seal the tire bead.
- Built to last**
 Heavy, solid 1/2 inch thick steel clamping table. Rugged steel reinforced chasis. All cylinders and valves can no rust. A compressed air lubricator and regulator is onboard to keep valves and cylinders maintenance free.
- EasyMont Pro bead assist**
 This patented devise holds the bead into the drop center allowing one operator to change low-profile, high performance and run-flat tires.

Hofmann manufactures a complete line of wheel service equipment.



4-wheel alignment systems



High performance wheel balancer with all automatic data entry.



Combination brake lathes for rotors, drums, and flywheels.

Specifications

Rim Clamping Diameter	10" - 24"
With optional adapters for	
Motorcycles/ATVs (EAA0329G53A)	8" - 23"
Inner clamping range	14" - 28"
Maximum rim width	15"
Maximum wheel diameter	47"
Bead breaker range	2" to 18"
Compressed air supply	100 to 170 psi @ 5 CFM
Bead loosening power	6,000 lbs
Work area dimensions H x W x D	85" x 68" x 72"
Packing dimensions H x W x D	70" x 42" x 56"
Shipping weight	805 lbs
Power supply	115 V / 1 phase / 50 - 60 Hz / 15 amps
	Other electricals available upon request
Drive motor	
Electric	U.S. Built 1 hp motor
Air	Available upon request

Optional Accessories

EasyMont bead assist device	EAA0329G35A
Quick change bead head kit	4028228
Protective insert for mount/demount head (10)	00087456
Composite mount/demount head, complete	EAA0247G20A
Replacement Composite head only	0024335
Outside clamping jaws protectors (set 4)	4027645
Protective slide cover (1)	0029455
Protective cover for tire lever	0024180
Snap-in jaw protectors (1)	0022129
Protective cover for bead breaker shovel	0026582
Wave Tire Tool	0025946
Rim Protector, snap's onto rim, use w/Wave Tool	4026853
Bead Clamp for performance wheels	6410190
Bead Clamp for run-flat tires	4024078
Magic Bead Pusher, use w/EasyMont	EAA0304G92A
Bead Breaker Disc, use with hex bar	EAA0304G43A

HOFMANN[®]
USA

309 Exchange Avenue • Conway, AR 72032
 (800) 251-4500 • (501) 450-1581
 Fax (501) 450-2085 • www.hofmann-usa.com

HOFMANN[®]
Canada

6500 Millcreek Drive • Mississauga, ONT L5N 4G4
 (800) 267-2185 • (866) 812-5316
 Fax (905) 821-2073 • www.hofmann.ca
 E-mail: info@hofmann.ca