HOFMANN®





Monty 4400

TIRE CHANGER

Monty 4400

HEAVY DUTY TIRE CHANGER FOR TRUCK, BUS AND MANY **OFF-ROAD APPLICATIONS.**

The Hofmann 4400 tire changer is designed to mount/demount all truck, bus, tractor, and off-the-road tires up to 90" in diameter.

Self-centering four jaw chuck

The hydraulically operated clamping jaws can clamp from 14"-44" either from the rim inner side or from the rim center bore. With optional jaw extentions up to 56".

One-man operation

The remote control console allows one person to safely monitor all tirechanging operations.

Patented mount/demount head assembly

The bead breaker disc and mount/demount heads are combined into one assembly for ease-of-use.

Versatility

The 3 HP 2 speed bi-directional chuck motor and heavy duty hydraulics allow the 4400 to handle the toughest tubeless, tube type, single or multi-piece wheels, Budd and Dayton rims.



Tire changer for over-the-road applications.

TIRE CHANGER

Specifications				
	200/230V	3 PH	50/6	

Shipping weight	2085 lbs.
Electric motors	200/230V, 3 PH, 50/60 Hz 20 amps
Hydraulic motor	2 HP
Chuck motor	3 HP
Chuck spindle dia	<u> </u>
Rim diameter	14" to 56"
Max. wheel width	43"
Max. tire diameter	90.5"
Rotational torque	2268 ft lbs.
Dimension	W x L x H 81" x 117" x 63"

Standard Accessories

Small tire tool	0001418
Large tire tool	4004461
Bead mounting lever	4002354
Mounting clamp	4009472

Optional Accessories

56" Jaw extentions	4019161
Bead roller	4022287
Alloy rim clamp	4021852
Protective alloy jaws (4)	4008257



Heavy duty wheel balancer for truck, bus, RV, and automobile/light truck tires.



309 Exchange Avenue • Conway, AR 72032 (800) 251-4500 • (501) 450-1581 Fax (501) 450-2085 • www.hofmann-usa.com



6500 Millcreek Drive . Mississauga, ONT L5N 4G4 (800) 267-2185 • (866) 812-5316 Fax (905) 821-2073 • www.hofmann.ca E-mail: info@hofmann.ca